

FEATURES

- Best picture quality (in combination with Digital LCD monitor)
- High resolution CCD camera (470,000 pixels)
- 1/3" Color CCD high resolution image sensor
- IP69K Waterproof Rating
- Diagonal 130° Viewing
- Normal/Mirror Image switching
- Ultra low light performance
- Automatic Electronic Iris
- Built-in Microphone
- Built-in IR LED's
- Built-in Automatic Heater (below +10°C)
- Temp. -40°C ~ 80°C
- Vibration resistant
- Waterproof screw type connector (IP67), 4-pin mini-DIN.
- E-mark.

Specifications

Image Sensor	1/3" Color SONY SUPER HAD II CCD
Scanning System	PAL 470,000 pixels
Resolution	520 TV Lines
S/N ratio	Minimum 44dB (at AGC off)
Minimum Illumination	0 lux (IR LED's on)
Power supply	DC 9 ~ 28V
Power Consumption	DC 12V, 475mA (Heater on) DC 12V, 245mA (Heater off)
Operating Temperature	-40°C to +80°C
Field of View angle	130° (Diagonal), 96.2° (Horizontal), 69° (Vertical)
Dimension	102(W) x 43(H) x 63(D) mm (camera only) 124(W) x 85(H) x 80(D) mm (incl. bracket & sunvisor)
Weight	326g (total weight incl. bracket & sunvisor: 464g)

